CONTEC

Stock Code:300869

CA10M-VET

Capnograph



Contec Medical Systems Co.,Ltd.

ADD:No.112 Qinhuang West Street, Economic & Technical Development Zone,
Qinhuangdao, Hebei Province, PEOPLE' S REPUBLIC OF CHINA
Tel: +86-335-8015430 Fax: +86-335-8015588
E-mail: cms@contecmed.com.cn Website: http://www.contecmed.com

CONTEC reserves the right of product appearance, specifications and function modification and updating, without prior notification.

Performance

• $ETCO_2$	
Measurement range	0 ~ 150 mmHg
Resolution	1 mmHg
Accuracy	0 ~ 40 mmHg：± 2 mmHg
	41 ~ 70 mmHg：± 5 % of readings
	71 ~ 100 mmHg：± 8 % of readings
	101 ~ 150 mmHg：± 10 % of reading
• Respiration rate	
Measurement range	2 ~ 150 rpm
Resolution	1 rpm
Accuracy	± 1 rpm
• Safety characteristic	
Degree of waterproof and dustproof	IP22
Type of protection against electric shock	internally powered equipment
Degree of protection against electric shock	type BF applied part
• Other parameters	
Preheat time	15 s
Response time	< 3 s
Alarm sound pressure level	50 dB
Working Hour	4 h

Physical characteristic

Dimension	59 mm × 56 mm × 59.5 mm
Weight:	92g (including batteries)
Gross weight of single piece	320g
Inner box size	136mm(L)×90mm(W)×107mm(H)
Outer box size	42.5cm(L)×35.5cm(W)×43cm(H)
Quantity	30 pieces
Gross weight	11kg

Operating environment

Temperature	5 °C ~ 40 °C
Relative humidity	30 % ~ 75 %, no condensation
Atmospheric pressure	700 hPa ~ 1060 hPa
Power supply	DC 3 V (2 AAA dry batteries)
Input power: ⩽ 1 VA	⩽ 1 VA

Accessories

User Manual	1book
Gas path adapter	1pcs
AAA batteries	2pcs