CONTEC

Stock Code:300869

SP750VET

Infusion Pump



Contec Medical Systems Co.,Ltd.

ADD:No.112 Qinhuang West Street, Economic & Technical Development Zone,
Qinhuangdao, Hebei Province, PEOPLE' S REPUBLIC OF CHINA
Tel: +86-335-8015430 Fax: +86-335-8015588
E-mail: cms@contecmed.com.cn Website: http://www.contecmed.com

CONTEC reserves the right of product appearance, specifications and function modification and updating, without prior notification.

Physical specification

Screen	2.8" TFT LCD
Weight	About 1.9 kg
Dimension	143.6 mm (L) × 151.8 mm (W) × 195.3 mm (H)

Parameter specification

Applicable IV set	Be compatible with multiple IV sets met standard requirements
Accuracy	± 5 %
Infusion rate	1 ~ 699 ml/h, increment: 1 ml/h
Preset volume	1 ~ 9999 ml, increment: 1 ml
Mode	Rate
KVO rate	1 ml/h
Occlusion pressure	3 grades, 100 ~ 300 kPa

Alarm

Alarm type	Audible and visual alarm
High-priority alarm	①Air bubble ②Occlusion ③Door open ④Motor failure ⑤Pressure failure ⑥Door failure ⑦Battery depletion ⑧Enter KVO
Low-priority alarm	①Standby prompt ②Near end ③Low battery

Battery

Battery type	Rechargeable Li-ion battery, 7.4 V/5000 mAh
Operating time	At least 4-hour continuous operation at the infusion rate of 25 ml/h after fully charged.
Charging time	The battery can be automatically charged when the device is connected to AC mains supply, it takes at least 8 ~ 12 hours to fully charge.

Interface

AC interface

Power supply

Power supply	100 -240 V~, 50/60 Hz

Work Environment

Temperature	+5 ~ +40 ℃
Relative humidity	20 ~ 90%
Atmospheric pressure	800 ~ 1060 hPa
Degrees of protection provided by enclosure	IPX2